



# Prescott SA

Prescott SA is a through-coloured semi aniline leather produced on South American hides. There may be holes and burn marks on this quality which attests to the authenticity of the leather.

Uses:

Furniture upholstery public environment, Furniture lining, Upholstery marine environment IMO

Average size (m²):	5 m²	Flexing resistance:	50000 (ISO 5402)
Thickness (mm):	1,2-1,4 mm	Colour fastness to rubbing - dry:	≥ 4 (ISO 11640)
Quality:	Semi aniline	Colour fastness to rubbing - wet:	≥ 4 (ISO 11640)
Råhudar:	SA	Color Fastness To Light:	≥ 5 (ISO 105-B02)
Fire test:	BS 5852 Crib 5, BS 5852 Source 0 & 1, Cal TB 117, EN 1021-1 & 2, IMO 2010 FTP Code Part 8	Colour fastness to rubbing - artificial sweat:	≥ 4 (ISO 11641)
Rivstyrka:	≥ 20 N (ISO 3377-1)	Adhesion - surface finish Dry:	≥ 2 N/10mm (ISO 11644)
		Adhesion - surface finish Wet:	≥ 2 N/10mm (ISO 11644)




Leather Prescott SA  
223 Swamp  
1110178



Leather Prescott SA  
289 Hezelnut  
1110180



Leather Prescott SA  
231 Chestnut  
1110221



Leather Prescott SA  
298 Root  
1110223



Leather Prescott SA  
208 Lamb  
1110254



Leather Prescott SA  
210 Greystone  
1110264



Leather Prescott SA  
211 Greyshadow  
1110265



Leather Prescott SA  
207 Black Ink  
1110266



Leather Prescott SA  
252 Volcano  
1110333



Leather Prescott SA  
0966 Snow White  
1110341



Leather Prescott SA  
292 Caffelatte  
1110331

## You control your data

We and our partners use technologies, including cookies, to collect information about you for various purposes, including:

- Necessary – makes the website usable.
- Statistics – help us understand how visitors interact with our website.
- Marketing – Used by advertisers to help us display relevant ads in other channels.

By clicking 'Accept All' you consent to all these purposes. You can also choose to indicate what purposes you will consent to using the custom selections and then click 'Accept selected'.

Decline All

Accept All

Necessary



Statistics



Marketing

